

## RESEARCH OUTPUTS / RÉSULTATS DE RECHERCHE

### **Extended abstract: Test them all, is it worth it? Assessing configuration sampling on the JHipster Web development stack**

Nuttinck, Alexandre; Acher, Mathieu; Devroey, Xavier; Perrouin, Gilles; Baudry, Benoit; Halin, Axel

*Published in:*

Proceedings of the 24th ACM Conference on Systems and Software Product Line

*DOI:*

[10.1145/3382025.3414985](https://doi.org/10.1145/3382025.3414985)

*Publication date:*

2020

*Document Version*

Peer reviewed version

[Link to publication](#)

*Citation for published version (HARVARD):*

Nuttinck, A, Acher, M, Devroey, X, Perrouin, G, Baudry, B & Halin, A 2020, Extended abstract: Test them all, is it worth it? Assessing configuration sampling on the JHipster Web development stack. in S Ali, WKG Assuncao, T Berger, C Cetina, P Collet, J Galindo, P Gazzillo, L Linsbauer, RE Lopez-Herrejon, S Nadi, S Schulze & S Trujillo (eds), *Proceedings of the 24th ACM Conference on Systems and Software Product Line*. ACM International Conference Proceeding Series, vol. Part F164267-A, ACM Press, pp. 302, 24th ACM Conference on Systems and Software Product Line, SPLC 2020, Virtual, Online, Canada, 19/10/20.  
<https://doi.org/10.1145/3382025.3414985>

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

#### **Take down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Extended abstract: Test them all, is it worth it? Assessing configuration sampling on the JHipster Web development stack

Axel Halin  
PReCISE, NaDI,  
Faculty of Computer Science,  
University of Namur  
Namur, Belgium

Xavier Devroey  
x.d.m.devroey@tudelft.nl  
Delft University of Technology  
Delft, The Netherlands

Alexandre Nuttinck  
alexandre.nuttinck@cetic.be  
CETIC  
Charleroi, Belgium

Gilles Perrouin  
gilles.perrouin@unamur.be  
PReCISE, NaDI,  
Faculty of Computer Science,  
University of Namur  
Namur, Belgium

Mathieu Acher  
mathieu.acher@irisa.fr  
IRISA, University of Rennes I  
Rennes, France

Benoit Baudry  
baudry@kth.se  
KTH Royal Institute of Technology  
Stockholm, Sweden

## ABSTRACT

This is an extended abstract of the article: Axel Halin, Alexandre Nuttinck, Mathieu Acher, Xavier Devroey, Gilles Perrouin, and Benoit Baudry. 2018. Test them all, is it worth it? Assessing configuration sampling on the JHipster Web development stack. In *Empirical Software Engineering* (17 Jul 2018). <https://doi.org/10.1007/s10664-018-9635-4>.

## CCS CONCEPTS

• **Software and its engineering** → **Software testing and debugging; Software product lines.**

## KEYWORDS

Configuration sampling, variability-intensive systems, software testing, JHipster, case study

### ACM Reference Format:

Axel Halin, Alexandre Nuttinck, Mathieu Acher, Xavier Devroey, Gilles Perrouin, and Benoit Baudry. 2020. Extended abstract: Test them all, is it worth it? Assessing configuration sampling on the JHipster Web development stack. In *24th ACM International Systems and Software Product Line Conference (SPLC '20)*, October 19–23, 2020, Montreal, QC, Canada. ACM, New York, NY, USA, 1 page. <https://doi.org/10.1145/3382025.3414985>

The assumption that it is impossible to test all configurations of a highly configurable software system motivates the development of many testing approaches. Such approaches rely on variability-aware abstractions and sampling techniques to cope with large configuration spaces. Yet, there is no theoretical barrier that prevents the exhaustive testing of all configurations by simply enumerating them if the effort required to do so remains acceptable.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

*SPLC '20*, October 19–23, 2020, MONTREAL, QC, Canada

© 2020 Copyright held by the owner/author(s). Publication rights licensed to ACM.  
ACM ISBN 978-1-4503-7569-6/20/10...\$15.00  
<https://doi.org/10.1145/3382025.3414985>

In this case study, we report on the first ever endeavor to test all possible configurations of the industry-strength, open source configurable software system: JHipster, a popular code generator for web applications.

In addition to providing a quantitative assessment of sampling techniques on all 26,257 configurations, we present numerous insights regarding the testing infrastructure and compare them with JHipster developers' practice: (1) a cost assessment and qualitative insights of engineering an infrastructure able to automatically test all configurations. This infrastructure is itself a configurable system and requires a substantial, error-prone, and iterative effort (8 man\*month); (2) a computational cost assessment of testing all configurations using a cluster of distributed machines. Despite some optimizations, 4,376 hours (~182 days) CPU time and 5.2 terabytes of available disk space are needed to execute 26,257 configurations; (3) a quantitative and qualitative analysis of failures and faults. We found that 35.70% of all configurations fail: they either do not compile, cannot be built or fail to run. Six feature interactions (up to 4-wise) explain this high percentage; (4) an assessment of sampling techniques. Dissimilarity and *t*-wise sampling techniques are effective to find faults that cause a lot of failures while requiring small samples of configurations. Studying both fault and failure efficiencies provides a more nuanced perspective on sampling techniques; (5) a retrospective analysis of JHipster practice. The 12 configurations used in the continuous integration for testing JHipster were not able to find the defects. It took weeks for the community to discover and fix the 6 faults; (6) a discussion on the future of JHipster testing based on collected evidence and feedback from JHipster's lead developers; (7) a feature model for JHipster v3.6.1 and a dataset to perform ground truth comparison of configuration sampling techniques, both available at <https://doi.org/10.5281/zenodo.3766690>.

Our work is the first endeavor to gather the ground truth of all possible configurations' failures of an industrial-strength open source project. Configuration failures represent one of the most common types of software failures; we believe our insights and data can support a much needed research in this direction.