

RESEARCH OUTPUTS / RÉSULTATS DE RECHERCHE

Analysis of equilibrium profiles in nonisothermal axial dispersion tubular reactors

Hastir, Anthony; LAMOLINE, Francois; WINKIN, Joseph; Dochain, Denis

Published in:
38th Benelux Meeting on Systems and Control

Publication date:
2019

Document Version
Peer reviewed version

[Link to publication](#)

Citation for pulished version (HARVARD):

Hastir, A, LAMOLINE, F, WINKIN, J & Dochain, D 2019, Analysis of equilibrium profiles in nonisothermal axial dispersion tubular reactors. in *38th Benelux Meeting on Systems and Control*.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Analysis of equilibrium profiles in nonisothermal axial dispersion tubular reactors

Anthony Hastir, François Lamoline, Joseph J. Winkin* and Denis Dochain†

* Namur Institute for Complex Systems (naXys) and Department of Mathematics,
University of Namur, Rempart de la vierge 8, B-5000 Namur, Belgium

† Institute of Information and Communication Technologies, Electronics and Applied Mathematics (ICTEAM),
Université Catholique de Louvain, Avenue Georges Lemaitre 4-6, B-1348 Louvain-La-Neuve, Belgium

anthony.hastir@unamur.be, francois.lamoline@unamur.be, joseph.winkin@unamur.be, denis.dochain@uclouvain.be

The dynamics of tubular reactors are governed by nonlinear partial differential equations (PDEs) derived from mass and energy balance equations. This includes plug flow and axial dispersion reactor models for which convection and/or diffusion are of interest. Nonlinearities in the dynamics are typically located in the kinetic terms and are based notably on the Arrhenius law for nonisothermal reactors, see [1].

Here, we are interested in tubular reactors involving a chemical reaction of the form $A \rightarrow B$ where A denotes the reactant and B the product. In the model, the state components are defined as the temperature (T [K]) and the concentration of reactant (C [mol/l]).

The equations of a nonisothermal tubular reactor are directly deduced from mass and energy balances on a slice of infinitesimal thickness dz during an infinitesimal time dt . They are given by

$$\begin{cases} \frac{\partial T}{\partial t} = -v \frac{\partial T}{\partial z} + \frac{\lambda_{ea}}{\rho C_p} \frac{\partial^2 T}{\partial z^2} - \frac{\Delta H}{\rho C_p} k_0 C e^{-\frac{E}{RT}} + \frac{4h}{\rho C_p a} (T_w - T), \\ \frac{\partial C}{\partial t} = -v \frac{\partial C}{\partial z} + D_{ma} \frac{\partial^2 C}{\partial z^2} - k_0 C e^{-\frac{E}{RT}}, \end{cases} \quad (1)$$

where $T(t, z)$ and $C(t, z)$ denote the temperature in the reactor and the concentration of the reactant respectively, in the reactor at time t and position z . Such equations are usually called convection – diffusion – reaction equations. See [1], [4] for the description of the parameters. To the PDEs (1), we associate specific boundary conditions, known as Danckwerts' conditions, which are given by $\frac{\lambda_{ea}}{\rho C_p} \frac{\partial T}{\partial z}(t, 0) = v(T(t, 0) - T_{in})$, $D_{ma} \frac{\partial C}{\partial z}(t, 0) = v(C(t, 0) - C_{in})$, $\frac{\partial T}{\partial z}(t, L) = 0$ and $\frac{\partial C}{\partial z}(t, L) = 0$. The variable T_w is due to a heat exchanger that acts along the whole spatial domain. Furthermore, the boundary variables $T_{in}(t)$ and $C_{in}(t)$ can be fixed at the inlet of the reactor.

From [2], tubular reactors are known to be well-posed, i.e. there exist unique state trajectories describing the temperature and the evolution of reactant concentration. Such considerations are based on state space and semigroup approaches.

The existence, the multiplicity and the stability of equilibrium profiles have been widely studied over the years, either on the nonlinear model with only the convection phenomenon or on the linear one involving mass axial dispersion.

More recently, in [3], an analysis of the multiplicity of equilibrium profiles of a tubular reactor with equal energy and

mass Peclet numbers was performed. These are dimensionless numbers representing the ratio between the convection transfer and the conduction transfer (thermal Peclet number, $\frac{vL\rho C_p}{\lambda_{ea}}$) or the ratio between the convection transfer and the diffusion transfer (mass Peclet number, $\frac{vL}{D_{ma}}$). Here, the main contributions are the extension of this study to the case of different or close Peclet numbers, see [4], and the statement of sufficient conditions for the equilibria to be exponentially stable in the case of equal Peclet numbers.

The aim of this research is to study the existence of equilibrium profiles for nonisothermal tubular reactors, to derive multiplicity criteria for these equilibrium profiles and to study their stability properties. It is shown that such reactors can exhibit different numbers of equilibrium profiles depending on parameters of the system, particularly on the diffusion coefficient, see [4]. Furthermore, it is shown that in the case of only one equilibrium profile, the latter is always exponentially stable and if three equilibria are exhibited, the pattern "exponentially stable – unstable – exponentially stable" is highlighted.

Acknowledgment

This research was conducted with the financial support of F.R.S-FNRS. Anthony Hastir is a FNRS Research Fellow under the grant ASP/DM - A676, FC 29535. François Lamoline is a FRIA Research Fellow under the grant F 3/5/5-MCF/BC. The scientific responsibility rests with its authors.

References

- [1] I. Aksikas, J.J. Winkin, and D. Dochain, "Optimal LQ-feedback regulation of a nonisothermal plug flow reactor model by spectral factorization", IEEE Transactions on Automatic Control, vol. 52, pp. 1179 – 1193, 07 2007.
- [2] M. Laabissi, M. Achhab, J.J. Winkin, and D. Dochain, "Trajectory analysis of nonisothermal tubular reactor nonlinear models", Systems and Control Letters, vol. 42, no. 3, pp. 169 – 184, 2001.
- [3] D. Dochain, "Analysis of the multiplicity of equilibrium profiles in tubular reactor models", IFAC-PapersOnLine, vol. 49, no. 18, pp. 903 – 908, 2016, 10th IFAC Symposium on Nonlinear Control Systems NOLCOS 2016.
- [4] A. Hastir, F. Lamoline, J.J. Winkin and D. Dochain, "Analysis of the existence of equilibrium profiles in nonisothermal axial dispersion tubular reactors", submitted.